

NTRGB150

Project :	Date :
Cat. No. :	Туре :
Notes :	Volts :

Applications :

NTRGB150 linear source consists of a high efficiency LED flexible ribbon producing saturated RGB lighting.


- Provides a programmable and variable multicolor lighting for reception halls, corridors and other venues.
- Create a decor or set a mood with the creation of a specific color and ambiance.
- Lights and easily colors surfaces such a walls, ceiling, niches, fescos, statures as well as enhances existing textures or architectural elements.
- Integrated task lighting, under cabinet lighting for studios or use it in merchandising showcases, shelving or in custom furniture projects.

The **NTRGB150** light heat production permits applications directly on wood, plexiglass or other types of plastics and glass surfaces.

While the **NTRGB150** does not require a heat dissipation surface it can be installed in our LED-BAR product line.

Consult our technical specs sheets to select one of our LEDBAR architectural linear profile.





Caracteristics:

- Red, green and blue modules integrated in all LED diodes.
- 30 diodes per meter/9 per foot.
- 7.2 Watts per meter / 2.2 Watts per foot
- Voltage 12VDC standard.
- 24 VDC on demand
- 5 meters / 16'4" maximum lenght per circuit.
- 120° degrees beam.
- 50,000 hours.
- IP22 standard

Linear Source Dimensions:

- 10 mm (0.39") wide X 2mm (0.08") high.
- IP67 version 13mm (0.51") wide.
- Lenght: 5 meters (16'4") per roll.
- Adhesive : Type 3M on back
- Cut every : 100mm 4" (3 LED) for 12 VDC 200mm 8" (6 LED) for 24 VDC
 Options :
- IP67 silicone envelope jacket.
- Dimming available consult factory
- Choices of wiring and connecting devices.
- Custom cutting services on tape and profiles available.





Ordering Matrix / Specification

Model	Strip	Color	Volts
NTRGB			
	150 150WP	Red, green, blue	12 VDC 24 VDC

The strip must be connected to a low voltage output power supply according to selected voltage and power criteria WP indicates a weatherproof strip inside a flexible silicone sleeve.

Natech Industrie

3154 boulevard Industriel, Laval, QC, H7L 4P7 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, info@natechlighting.com

This specification is valid as of 2015-08 and is subject to change without notice. Please confirm with the manufacturer before placing an order. Copyright 2014 Natech Industrie. All rights reserved.