

Project :

Date :

Cat. No. :

Type :

Notes :

Volts :

The NTWL-RD/SQ-1W recessed wall series are available round or square 1W LED sources, suitable for all residential and commercial installations. Applications for a range from cabinet, millwork, closet, corridor to stairs.

<b>Application:</b>	Stairs, furniture, cabinet, corridor	
<b>Light color:</b>	5000K white	95lm
	4100K natural white	90lm
	3000K warm white	85lm
<b>Fixture finish:</b>	Anodized aluminum	
<b>Fixture material:</b>	Aluminium	
<b>Optic:</b>	45° model NTWL-RD/SQ-1W-45-XX	
	120° model NTWL-RD/SQ-1W-120-XX	
<b>Voltage:</b>	350 MA	
<b>Lamp life:</b>	50,000 hours	
<b>Maximum wattage:</b>	1.245 Watt	
<b>Fixation:</b>	Spring clips	
<b>Working temperature:</b>	-30 - +55°C	
<b>Certification:</b>	Conform to ANSI/UL standard 2108 Certified to CAN/CSA standard 22.2-9.0	
<b>Driver constant current class II recommended:</b>		
<b>NTLD3W-350MA-12</b>	source 12V	1 to 3 units
<b>NTLD350MA</b>	for 120VAC	1 to 6 units
<b>NTLD350MA-WP</b>	for 120VAC	1 to 6 units


\* For dimming or control option, please consult factory

### Ordering Matrix / Specification


Model	Type	Wattage	Beam	Color
NTWL		1W		
	RD (round) SQ (square)		45 (45 degrees) 120 (120 degrees)	WH (white) NW (natural white) WW (warm white)





NTWL-RD-1W-45-XX




NTWL-SQ-1W-45-XX



NTWL-RD-1W-120-XX



NTWL-SQ-1W-120-XX



### Natech Industrie

3154 boulevard Industriel, Laval, QC, H7L 4P7 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, info@natechlighting.com

This specification is valid as of 2015-08 and is subject to change without notice. Please confirm with the manufacturer before placing an order.  
Copyright 2014 Natech Industrie. All rights reserved.