

Project :

Date :

Cat. No. :

Type :

Notes :

Volts :

Applications:

Ideal for areas where intelligent LED solutions are required.

- For decor, ambiance and public safety.
- Architectural accentuation with warm and cool white.

Suitable for indoor architectural, hospitality, commercial and residential applications.

Look for other LEDIX IP56 rated products for outdoor applications.

Housing:

Stainless steel housing polished or painted aluminium precision fit parts and assembly.

Source:

- 0.56W Cool white LED source
- 0.42W Warm white LED source
- 0.28W In single color source
 - RED = 630nm
 - Green = 520nm
 - Blue = 459nm

Finish:

Available in:

- Polished stainless steel finish
- Silver aluminium powder coated
- Graphite powder coated aluminium
- Old gold powder coated aluminium
- White
- Black

Options:

Choose one of the following

1. Standard (IP44)

Mounting:

Standard Tico series can be surface mount only.

Certification :

Conforms to ANSI/UL standard UL-2108
 Certified to CAN/CSA standard 22.2-9.0

Power supply requirements:

Requires a 12VDC output power supply and can also operate with a 14VDC source for automotive or RV applications.


Leads, connectors and power supply are supplied separately.





04 Standard



05 Standard



05 Standard



04 Standard

Ordering Matrix / Specification

Model	Type	Installation	Voltage	Function(s)	Finish color	Color
NTWL			1 (12volts)			
	04= Tico 05= Tico (with square plate)	1- Surface		1- Standard	1- Aluminium 2- Stainless steel 3- Graphite 4- Old gold 5- White 6- Black	1- White 2- Warm white 3- Red 4- Green 5- Blue



Natech Industrie

3154 boulevard Industriel, Laval, QC, H7L 4P7 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, info@natechlighting.com

This specification is valid as of 2015-08 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
 Copyright 2014 Natech Industrie. All rights reserved.