

# NTWL-01-XXX-XX

Project :	Date :
Cat. No. :	Туре :
Notes :	Volts :

## **Applications:**

Ideal for areas where intelligent and RGB LED solutions are required.

- For decor, ambiance and public safety.
- Architectural accentuation with warm and cool white or ambiance creation with RGB versions.
- Motion and twilight detection for patios, pool decks, corridors and bathrooms.
- Battery back-up for emergency path of egress.
- Remote control operation available.

Suitable for indoor architectural, hospitality, commercial and residential applications.

Look for other LEDIX IP56 rated products for outdoor applications.

#### Housing:

Stainless steel housing polished or painted aluminium precision fit parts and assembly. Saddle mount PIR motion sensor available and semi recessed battery backup module.

#### Source:

- 0.56W Cool white 5900K 19 lumens 0.42W Warm white 3100K 13 lumens
- 0.28W In single color source
- RED = 630nm
- Green = 520nm
- Blue = 459nm
- 0.84W For RGB

## Finish:

- Available in:
- Polished stainless steel finish
- Silver aluminium powder coated
- Graphite powder coated aluminium
  - Old gold powder coated aluminium
- White
- Black

#### Options:

Choose one of the following:

- 1. Standard (IP44)
- 2. Built-in PIR motion sensor (IP20)
- 3. Built-in battery backup (IP20)

## Mounting:

Standard Moza series can be surface mount or semi-recessed with options such as motion sensor, battery backup,

## **Certification :**

Conforms to ANSI/UL standard UL-2108 Certified to CAN/CSA standard 22.2-9.0

### Power supply requirements:

Requires a 12VDC output power supply and can also operate with a 14VDC source for automotive or RV applications.


Leads, connectors and power supply are supplied separately.

RGB external controller needed sold separately.





01-standard

73









## **Ordering Matrix / Specification**

 Nodel	Туре		Installation	Voltage	Function(s)	_	Finish color	Color	
NTWL	- 01		-	<b>1</b> (12volts)		]-			
	01= Mo	za	1- Surface 2- Semi-recessed		<ol> <li>Standard</li> <li>Built-in PIR motion sensor</li> <li>Built-in battery backup</li> </ol>		<ol> <li>Aluminium</li> <li>Stainless steel</li> <li>Graphite</li> </ol>	1- White 2- Warm white 3- Red	Æ
					* For led controller ask factory		4- Old gold 5- White 6- Black	4- Green 5- Blue 6- RGB	c Usrev Us Intertek 4010322