

Project :

Date :

Cat. No. :

Type :

Notes :

Volts :



**Constant current Led driver
Class II
350/700MA wall plug**



SELECTION GUIDE

NTLD350MA-WP 100-240Vac / 1-8W 350ma Constant Current LED driver

NTLD700MA-WP 100-240Vac / 3-9W 700ma Constant Current LED driver


ELECTRICAL CHARACTERISTICS

Parameter	Symbol	NTLD350MA-WP	NTLD700MA-WP
Input Voltage	Vin	100V-240Vac	100V-240Vac
Input Frequency	F	50Hz/60Hz	50Hz/60Hz
Output Voltage	Vo	3-36Vdc	3-21Vdc
Output Power	Po	1-8W	3-9W
Output Current	Io	350ma ± 6%	700ma ± 6%

ENVIRONMENTAL RATINGS

Parameter	Symbol	Minimum	Maximum
Operating temperature	Top	-10°C	+40°C
Storage temperature	Tst	-20°C	+80°C

MECHANICAL DIMENSIONS (mm & inches)



CONFITURATION ARRAYS WHEN USING HI POWER LEDs

with the 350ma output current

with the 700ma output current

NTLD350MA-WP driver at 350ma/LED: from 1 to 8 LEDs in series

NTLD700MA-WP driver at 700ma/LED: from 1 to 2 LEDs in series

