

Project :

Date :



Cat. No. :

Type :

Notes :

Volts :

This product combines your LED power supply and dimming control into a single compact unit designed to simplify design installation and eliminate compatibility issues between LED drivers and switches



Model	OTM-BD120-12-D	OTM-BD160-24-D	
Certificate	UL / cUL / FCC / Class P / SELV / RoHS / Reach		
Output	DC Rate Voltage	12V (12V-13.5V adjust by knob)	24V (24V-26V adjust by knob)
	Voltage Tolerance	±0.5V	
	Load Regulation	≤2%	≤1%
	Line Regulation	≤0.5%	
	Rated current	10A	6.67A
	Rated power	120W	160W
	Voltage Ripple	3%	2%
Input	Voltage Range	120VAC	
	Frequency Range	60Hz	
	Power Factor @ full load	0.99	
	THD(Typ.) @ full load	≤10%	
	Efficiency @ full load	93.3%	94.5%
	AC Current (Max.)	1.1A	1.5A
	Inrush Current (Typ.)	54A, 290us@50%peak	
	Leakage current	<0.5mA	
Short Circuit	Hiccup mode, recovers automatically after fault condition is removed		

Fit with Box 3104

Or double box

Natech Industrie

1995 Francis Hughes, Laval, QC, H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-10 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.