

Project :	Date :
Cat no. :	Type :
Notes :	Volts :

Description:

The **NTALB-04R** LED bar design provides a unique linear lighting solution combining style, performance and durability while reducing construction and operating costs through installation time, energy savings and a maintenance free application. Ideal for surface installations.

Housing:

The **NTALB-04R** is a high precision extruded anodized aluminum bar that can accept a low-power LED source to medium power.

Lens:

Precision fit extruded acrylic for indoor use only available in:

- FR** Frosted
- OP** Opal (white)
- BK** Black PC

Mounting:

Mounts within on a surface with:

- FC** Fixed clips (set of 2)
- SW** Swivel clips (set of 2)
- MG** Magnet (unit)

Application/Installation:

The **NTALB-04R** LED bar can be installed, for up, or down applications. This bar can be installed on surfaces, under cabinets.

Voltage:

- 12 VDC
- 24 VDC

Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80).

All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.


Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.

Homologation:

Conforms to ANSI/UL standard UL-2108
Certified to CAN/CSA standard 22.2-9.0



NTALB04R-BK



FC



SW



MG

Ordering Matrix / Specification


Model	Bar	Length	Lens	Mounting	LED**	Color	Volts
NTALB							
	04R (aluminium) 04RBK (black)	1000 mm 2000 mm XX mm*	FR Frosted OP Opal BK Black PC	FC Fixed Clips SC Swivel Clip MG Magnet	UT30 (4.6W/M 450LM) UT30 WP UT60 (10W/M 896LM) UT60 WP	VWW (2400K) WW (2700, 3000, 3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
					HP30 (14.5W/M 1279LM) HP60 (10W/M 1079LM)	WW (3000K) NW (4100K) WH (5000K)	12VDC 24VDC
					HP7.2 (7.2W/M 1008LM) HP10 (10W/M 1450LM) HP120 (19.2W/M 1600LM) VHP64 (22W/M 3437LM)	WW (3000K) NW (4100K) WH (5000K)	24VDC
					CCT HP304 (14W/M 560-700LM) UT39K (30W/M 790-830LM)	(2700-6500K)****	
					RGB 150 (7.2W/M) RGB 300 (14.4W/M) RGB 840 (14.4W/M)		
					RGBW192 (15.3W/M 343LM)		

* Consult factory for special lengths

** Consult the LED linear source and driver data sheets for available wattages and characteristics

*** Consult Factory

**** Color Correction



Natech Industrie

1995 Francis Hughes, Laval, Qc H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

Cette spécification est valide en date du 2022-09 et est sujette à changement sans préavis. Veuillez confirmer avec le manufacturier avant de placer une commande. Droit de reproduction ©2014 Natech Industrie. Tous droits réservés.