

Project :

Date :

Cat. No :

Type :

Notes :

Volts :

Description:

The **NTALB-06** LED bar design provides a unique linear lighting solution combining style, performance and durability while reducing construction and operating costs through installation time, energy savings and a maintenance free application.

Housing:

The **NTALB-06** is a high precision extruded anodized aluminum "L" shaped bar that can accept a LED linear source from normal to medium power.

Lens:

Precision fit extruded acrylic snap-in "L" shaped diffusing lens available in:

FR Frosted

OP Opal (white)

BK Black PC

Mounting:

Mounts directly on the surface

FC Fixed clips (set of 2, "L" shaped)

Application/Installation:

The **NTALB-06** LED bar can be installed, for up or down applications or combined in multidirectional applications, even combining up-down lighting with different light ratios.

Consult factory for damp application or splash area using our silicone jacketed IP67 sources. (WP)

Voltage:

12 VDC

24 VDC

Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 50,000 hours (L70).

All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.

Homologation:

Conforms to ANSI/UL standard UL-2108

Certified to CAN/CSA standard 22.2-9.0




NTALB06 - FR



NTALB06 - OP



NTALB06 - End Caps



NTALB06-BK

Ordering Matrix / Specification

Model	Bar	Length	Lens	Mounting	LED**	Color	Volts
NTALB	06						
	06 (aluminium) 06BK (black)	1000 mm 2000 mm XX mm*	FR Frosted OP Opal BK Black PC	FC Fixed Clips	UT30 (4.6W/M 450LM) UT30 WP UT60 (10W/M 866LM) UT60 WP	VWW (2400K) WW (2700, 3000, 3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC

* Consult factory for special lengths.



Natech Industrie

1995 Francis Hughes, Laval H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-09 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.